



MiniNVR видеорекордери

	MiniClient	MiniNVR	MiniNVR-4P	MiniNVR Hybrid
Тип на устройството	Remote workstation	NVR	NVR	Hybrid
Операционна система	Клиентска версия TRASSIR OS (Linux)	TRASSIR OS (Linux)	TRASSIR OS (Linux)	TRASSIR OS (Linux)
Максимален брой канали	изобразява 32 канала записва 32 канала NetREC	16	16 (4 PoE портове)	18
Скорост на запис	256 Mbit/s	256 Mbit/s	256 Mbit/s	256 Mbit/s
Резолуция	до 5 Mpix	до 5 Mpix	до 5 Mpix	до 5 Mpix
Видео изходи	1 x VGA 1 x HDMI	1 x VGA 1 x HDMI	1 x VGA 1 x HDMI	1 x VGA 1 x DVI-I 1 x HDMI
Аларма Вход /Изход	NetPing Ethernet IO устройства	NetPing Ethernet IO устройства	NetPing Ethernet IO устройства	NetPing Ethernet IO устройства
SATA HDD	SATA HDD 2 x 3,5“ HDD 8 TB Support	SATA HDD 2 x 3,5“ HDD 8 TB Support	SATA HDD 2 x 3,5“ HDD 8 TB Support	SATA HDD 2 x 3,5“ HDD 8 TB Support
Rack Mount	Rack Mount 1U, 19“	Rack Mount 1U, 19“	Rack Mount 1U, 19“	Rack Mount 1U, 19“
Размери	440 x 293,6 x 44,5 mm	440 x 293,6 x 44,5 mm	440 x 293,6 x 44,5 mm	200 x 160 x 355 mm
Технологии	Свързва се с неограничен брой TRASSIR сървъри Записва 4 NetREC мрежови канала	ActiveSearch, MultiSearch, MultiStor, Failover, Mobile Client, Client Cloud, HeatMaps, Recovery, Fire & Smoke, Face Detector, Sabotage Detector, Plans PTZ, EventSearch	ActiveSearch, MultiSearch, MultiStor, Failover, Mobile Client, Client Cloud, HeatMaps, Recovery, Fire & Smoke, Face Detector, Sabotage Detector, Plans PTZ, EventSearch	ActiveSearch, MultiSearch, MultiStor, Failover, Mobile Client, Client Cloud, HeatMaps, Recovery, Fire & Smoke, Face Detector, Sabotage Detector, Plans PTZ, EventSearch
Опционални технологии	Записва до 32 NetREC мрежови канала	ActiveDome PeopleCounter ActivePOS	ActiveDome PeopleCounter ActivePOS	ActiveDome PeopleCounter ActivePOS



DuoStation видеорекодрери

	DuoStation	DuoStation Hybrid	DuoStation-16P
Тип на устройството	NVR	Hybrid	NVR
Операционна система	TRASSIR OS (Linux)	TRASSIR OS (Linux)	TRASSIR OS (Linux)
Максимален брой канали	32	total - 32 (up to 16 analogchannels)	total -32 (16 PoE ports)
Скорост на запис	512 Mbit/s	512 Mbit/s	512 Mbit/s
Резолюция	до 5 Mpix	до 5 Mpix	до 5 Mpix
Видео изходи	4 x 3.5" 8 TB HDD поддържа HotSwap	4 x 3.5" 8 TB HDD поддържа HotSwap	4 x 3.5" 8 TB HDD поддържа
Rack монтаж	-	-	Rack Mount 1,5U, 19"
Размери	315 x 208 x 198 mm	315 x 208 x 198 mm	440 x 390 x 70 mm
Технологии	ActiveSearch, MultiSearch, MultiStor, Failover, Mobile Client, Client Cloud, HeatMaps, Recovery, Fire & Smoke, Face Detector, Sabotage Detector, Plans PTZ, EventSearch	ActiveSearch, MultiSearch, MultiStor, Failover, Mobile Client, Client Cloud, HeatMaps, Recovery, Fire & Smoke, Face Detector, Sabotage Detector, Plans PTZ, EventSearch	ActiveSearch, MultiSearch, MultiStor, Failover, Mobile Client, Client Cloud, HeatMaps, Recovery, Fire & Smoke, Face Detector, Sabotage Detector, Plans PTZ, EventSearch
Опционални технологии	ActiveDome PeopleCounter ActivePOS	ActiveDome PeopleCounter ActivePOS	ActiveDome PeopleCounter ActivePOS



QuattroStation видеорекодери

	QuattroStation	QuattroStation Pro
Тип на устройството	NVR	NVR
Операционна система	TRASSIR OS (Linux)	TRASSIR OS (Linux)
Максимален брой канали	64	128
Скорост на запис	700 Mbit/s	700 Mbit/s
Резолюция	5 Mpix и повече	5 Mpix и повече
Видео изходи	1 x VGA 1 x DVI-I 1 x HDMI	2 x VGA 2 x DVI-I 2 x HDMI
Аларма	8 x 3.5"	8 x 3.5"
Вход /Изход	8TB HDD поддържа	8TB HDD поддържа HotSwap
Rack монтаж	Rack Mount 4U, 19"	Rack Mount 4U, 19"
Размери	550x430x176 mm	648x452x178 mm
Технологии	ActiveSearch MultiSearch MultiStor Failover Mobile Client Client Cloud	HeatMaps Recovery Fire & Smoke Face Detector Sabotage Detector Plans PTZ EventSearch Informer
Опционални технологии	ActiveSearch+ ActiveDome+ People Counter People Counter Pro Kinetic Map Shelf Detector ActivePOS AutoTRASSIR SIMT	ActiveSearch+ ActiveDome+ People Counter People Counter Pro Kinetic Map Shelf Detector ActivePOS AutoTRASSIR SIMT



UltraStation видеорекодери

	UltraStation 16	UltraStation 24	UltraStation 36
Тип на устройството	NVR с повишена надеждност	NVR с повишена надеждност	NVR с повишена надеждност
Операционна система	Windows Embedded OS	Windows Embedded OS	Windows Embedded OS
Максимален брой канали	128	256	256
Скорост на запис	700 Mbit/s	700 Mbit/s	700 Mbit/s
Резолуция	5 Mpix и повече	5 Mpix и повече	5 Mpix и повече
Видео изходи	1 x VGA 1 x DVI-D 1 x HDMI	1 x VGA 1 x DVI-D 1 x HDMI	1 x VGA 1 x DVI-D 1 x HDMI
Аларма Input / Outputs	NetPing Ethernet IO устройства	NetPing Ethernet IO устройства	NetPing Ethernet IO устройства
SATA HDD	16 x 3,5“HDD 6 TB Поддържа HotSwap	24 x 3,5“HDD 6 TB Поддържа HotSwap	Повишена надеждност 36 x 3,5“ HDD 6 TB Поддържа HotSwap
Rack монтаж	Rack Mount 3U, 19“	Rack Mount 4U, 19“	Rack Mount 4U, 19“
Размери	132 x 437 x 648 mm	178 x 437 x 660 mm	178 x 437 x 699 mm
Технологии	ActiveSearch MultiSearch MultiStor Failover Mobile Client Client Cloud HeatMaps Recovery Fire & Smoke Face Detector Sabotage Detector Plans PTZ EventSearch Informer	ActiveSearch MultiSearch MultiStor Failover Mobile Client Client Cloud HeatMaps Recovery Fire & Smoke Face Detector Sabotage Detector Plans PTZ EventSearch Informer	ActiveSearch MultiSearch MultiStor Failover Mobile Client Client Cloud HeatMaps Recovery Fire & Smoke Face Detector Sabotage Detector Plans PTZ EventSearch Informer
Опционални технологии	ActiveSearch+, ActiveDome+, People Counter, People Counter Pro, Kinetic Map, Shelf Detector, ActivePOS, AutoTRASSIR, SIMT	ActiveSearch+, ActiveDome+, People Counter, People Counter Pro, Kinetic Map, Shelf Detector, ActivePOS, AutoTRASSIR, SIMT	ActiveSearch+, ActiveDome+, People Counter, People Counter Pro, Kinetic Map, Shelf Detector, ActivePOS, AutoTRASSIR, SIMT
Допълнителни	RAID 5 (Възможно е да поддържа и други RAID технологии) Захранващо устройство с двойна резервираност	RAID 5 (Възможно е да поддържа и други RAID технологии) Захранващо устройство с двойна резервираност	RAID 5 (Възможно е да поддържа и други RAID технологии) Захранващо устройство с двойна резервираност

What is included in TRASSIR Ecosystem?

